

FILTROS PARA RECOGIDA DE IMPUREZAS

| Referencia | Pulgadas |
|-------------|----------|
| Ref. 790001 | 1/2" |
| Ref. 790002 | 3/4" |
| Ref. 790003 | 1" |
| Ref. 790004 | 1 1/4" |
| Ref. 790005 | 1 1/2" |
| Ref. 790006 | 2" |
| Ref. 790007 | 2 1/2" |
| Ref. 790008 | 3" |
| Ref. 790009 | 4" |



CARACTERÍSTICAS DE CONSTRUCCIÓN

- **Cuerpo** de 1/2" a 1 1/4" CW617N.
- **Cuerpo** de 1 1/2" a 2 1/2" CB7535.
- **Cuerpo** de 3" a 4" bronce.
- **Malla** de acero inox. AISI 304.
- **Junta tórica** NBR shore 70.
- **Rosca** gas DIN 259.
- **Grado de filtración** estandar 0,5mm.

| Rosca Gas | 1/2" | 3/4" | 1" | 1 1/4" | 1 1/2" | 2" | 2 1/2" | 3" | 4" |
|-----------|------|------|-----|--------|--------|------|--------|------|------|
| PN | 16 | 16 | 16 | 16 | 16 | 16 | 16 | 16 | 16 |
| H (mm) | 34 | 42 | 50 | 63 | 70 | 87 | 108 | 148 | 150 |
| L (mm) | 52 | 63 | 75 | 91 | 102 | 118 | 150 | 167 | 226 |
| P/gr | 115 | 185 | 320 | 515 | 665 | 1195 | 1930 | 3770 | 6700 |
| Nº/P/C | 160 | 126 | 60 | 30 | 24 | 12 | 8 | 5 | 2 |

